



Wall Bracket

Sliding Cross Bar Provides Exceptional Width Range

Code	Description	Qty
13170 (AU450)	Wall Bracket – powder coated	6
13171 (AU550)	Wall Bracket – powder coated	4

FEATURES

- Strong secure support
- Powder coat finish
- Includes level for convenience
- Complete with fasteners, nuts & bolts
- Pre-assembled ready for quick installation

Max Load Capacity

AU450 - 100kg

AU550 - 150kg



AU450

Bottom Bar: 450
Vertical Bar: 350
Cross Bar: 700
Thickness: 1.5
Loading(kg): 100

AU550

Bottom Bar: 550
Vertical Bar: 450
Cross Bar: 850
Thickness: 1.8
Loading(kg): 200

Roof Bracket

Sliding Cross Bar Provides Exceptional Width Range

Code	Description	Qty
13172 (HP049C)	Adjustable Roof Bracket – Powder Coated	4

FEATURES

- Powder coated finish
- Complete with fasteners, nuts & bolts
- Adjustable angle to suit all applications

Max Load Capacity

HP049C - 200kg



HP049C

Length: 1000
Width: 500
Supporting Bar1: 500
Supporting Bar2: 230
Thickness: 2
Loading(kg): 200

PVC Mount Blocks

Air Conditioner Support Blocks

Code	Description	Set
13173 (Q350)	PVC Mount Blocks 350	1
13174 (Q450)	PVC Mount Blocks 450	1

FEATURES

- PVC Material
- UV-resistant
- Complete with bolts & nuts

*Each set contains 2 x Mount Blocks



Q350

Length: 350
Width: 105
Height: 95mm
NW: 1.1kg
GW: 1.3kg
Loading capacity: 150kg

Q450

Length: 450
Width: 105
Height: 95mm
NW: 1.42kg
GW: 1.62kg
Loading capacity: 150kg



Polyslab

Air Conditioner and Equipment Bases

Code	Description	Load Rating
12905	1130 x 650 x 51mm - 6.5kg	160kg
12904	885 x 465 x 51mm - 2.4kg	160kg
12903	640 x 340 x 51mm - 1.6kg	120kg

FEATURES

- Australian made
- Made of recycled materials
- Eco-friendly & UV resistant
- Impact resistant & ultra lightweight
- Supports all split system air conditioning units
- Stackable design

APPLICATION

Lightweight universal polymer equipment base for hot water systems • For indoor and outdoor use

RECOMMENDED FOR

Supporting split system air conditioning units and equipment



Drain Hose

Mini-split Condensate Drain Hose

Code	Description	Qty
13175 (GH-7004A)	Drain Hose	1

FEATURES

- UV-resistant
- 50m Roll
- Cut to length
- Convenient storage carton



Length: 50m/Roll
16mm ID / 21mm OD

StrutFoot

SBR Recycled Rubber Feet

Code	Description	Qty
13139 (SF4025-SFR 250)	Rubber Feet Inc Channel 250	1
13140 (SF4040-SFR 400)	Rubber Feet Inc Channel 400	1
13141 (SF4060-SFR 600)	Rubber Feet Inc Channel 600	1
13142 (SF4010-SFR 1000)	Rubber Feet Inc Channel 1000	1
13143 (SF4525-SFR 250 Low)	Rubber Feet Inc Channel	1
13144 (SF4540-SFR 400 Low)	Rubber Feet Inc Channel	1
13145 (SF1560-SFR 600 High Block)	Rubber Feet Inc Channel High Block 600	1
13146 (SF1512-SFR 1200 High Block)	Rubber Feet Inc Channel High Block 1200	1

FEATURES

- Recycled SBR from truck tyres
- Compatible with Unistrut systems
- Robust and weighted product to reduce product movement on roof
- Pre galvanised channel
- Practical and versatile 6-feet range for pipe work and cable trays
- For smaller outdoor condensing units or air source heat pump installations
- Vibration and noise absorption

*Unistrut not included



SF4025
Length: 250
Width: 180
Height: 95 mm
Max load: 160kg

SF1512
Length: 1200
Width: 130
Height: 150 mm
Max load: 645kg



For more information on our product limited warranty, visit RectorSeal.com

www.ventilationsolutions.com.au



Ph: 1300 998 326
Fax: 02 9675 6606